

## Lifts

With the right lift, you'll get the most out of your touchscreen. Want it to stay steady on the wall? Or do you want to tilt and move it around? Whatever you need, we have the right lift for it.



	All-in-One lift (late 2015 model)	Mobile Lift	Wall Lift
Min height vertical position	989 mm / 38.94 inches	1192 mm / 46.93 inches	1283 mm / 50.51 inches
Min height horizontal position	664 mm / 26.14 inches	N/A	N/A
Max. height vertical position	1649 mm / 64.92 inches	1852 mm / 72.91 inches	2138 mm / 84.17 inches
Max. height horizontal position	1324 mm / 52.13 inches	N/A	N/A
Measurements, ground surface	570 x 600 mm / 22.44 x 23.62 inches	570 x 600 mm / 22.44 x 23.62 inches	550 x 125 mm / 21.65 x 4.92 inches
Range	660 mm / 25.98 inches	660 mm / 25.98 inches	675 mm / 26.57 inches
Tilt	90°	N/A	N/A
Max lift weight	75 kg / 165.35 lbs	110 kg / 242.51 lbs	110 kg / 242.51 lbs
Applies to	Prowise 42", 55" and 65"	All Prowise screens	All Prowise screens
Wheels	Swivel castor with directional lock, housing made from high grade synthetic materials with metal parts made of Stainless Steel, double ball bearing swivel head	Swivel castor with directional lock, housing made from high grade synthetic materials with metal parts made of Stainless Steel, double ball bearing swivel head	N/A
Wheel diameter	125 mm / 4.92 inches	125 mm / 4.92 inches	N/A
Power	~ 100-120 V (50/60Hz) and ~ 220-240 V (50/60Hz)	~ 100-120 V (50/60Hz) and ~ 220-240 V (50/60Hz)	~ 100-120 V (50/60Hz) and ~ 220-240 V (50/60Hz)
Stand-by power consumption	0,1 Watt	0,1 Watt	0,1 Watt
Duty cycle columns	10% ~ 6 min. of 2 minutes continuous use followed by 18 minutes not in use.	10% ~ 6 min. of 2 minutes continuous use followed by 18 minutes not in use.	10% ~ 6 min. of 2 minutes continuous use followed by 18 minutes not in use.
Duty cycle actuator	10% ~ 6 min. of 2 minutes continuous use followed by 18 minutes not in use.	N/A	N/A
Soft Start / Stop function	Yes	Yes	Yes

Noise level	Low	Low	Low
Protection against overload (EOP)	Yes	Yes	Yes
Anti-Collision TM (software)	No	No	Yes
Column with integrated anti-collision sensor	Yes	Yes	No
Materials	Steel	Steel	Steel
Color	RAL 9006 (column) and RAL 9005 (basebox)	RAL 9006 (column) and RAL 9005 (basebox)	RAL 9006
Keyboard storage included	No	Yes	Yes
UTP config-port	Yes	Yes	No
Hand control remote	Yes	No	No
Keypad	No	Yes	Yes
Certifications	CE	CE	CE
Warranty	5 year	5 year	5 year
Gross Weight	59 kg / 130.07 lbs	64 kg / 141.1 lbs	45 kg / 99.21 lbs
Netto Weight	56 kg / 123.46 lbs	55 kg / 121.25 lbs	41 kg / 90.39 lbs
Dimensions of the total packing (W x H x D)	660 x 322 x 573 mm / 25.98 x 12.68 x 22.56 inches	972 x 574 x 715 mm / 38.27 x 22.6 x 28.15 inches	1255 x 590 x 220 mm / 49.41 x 23.23 x 8.66 inches

